


Trilho vignole (trilho ferroviário)

Wirth | Rail



| | Peso | | Boleto A | | Altura H | | Patim B | | Alma S | | |
|--------------------------|----------------|--------|----------|-------|----------|--------|---------|--------|--------|-------|-------|
| | kg/m | lb/yda | mm | pol. | mm | pol. | mm | pol. | mm | pol. | |
| Perfis americanos | | | | | | | | | | | |
| AREMA 2001 | 141RE (TR70) | 69.79 | 140.68 | 77.79 | 3 1/16 | 188.91 | 7 7/16 | 152.40 | 6 | 17.46 | 11/16 |
| | 136RE (TR68) | 67.41 | 135.88 | 74.61 | 2 15/16 | 185.74 | 7 5/16 | 152.40 | 6 | 17.46 | 11/16 |
| | 133RE | 66.10 | 133.25 | 76.20 | 3 | 179.39 | 7 1/16 | 152.40 | 6 | 17.46 | 11/16 |
| | 132RE | 65.31 | 131.66 | 76.20 | 3 | 180.98 | 7 1/8 | 152.40 | 6 | 16.67 | 21/32 |
| | CB122 | 60.77 | 122.50 | 74.61 | 2 15/16 | 172.24 | 6 25/32 | 152.40 | 6 | 16.67 | 21/32 |
| | 119RE | 58.87 | 118.67 | 67.47 | 2 21/32 | 173.04 | 6 13/16 | 139.70 | 5 1/2 | 15.88 | 5/8 |
| ASTM A1/2000 | 115RE (TR57) | 56.89 | 114.68 | 69.06 | 2 23/32 | 168.28 | 6 5/8 | 139.70 | 5 1/2 | 15.88 | 5/8 |
| | 100RE (TR50) | 50.35 | 101.50 | 68.26 | 2 11/16 | 152.40 | 6 | 136.53 | 5 3/8 | 14.29 | 9/16 |
| | 100ARA-B | 49.88 | 100.56 | 67.47 | 2 21/32 | 143.27 | 5 41/64 | 130.57 | 5 9/64 | 14.29 | 9/16 |
| | 100ARA-A | 49.80 | 100.39 | 69.85 | 2 3/4 | 152.40 | 6 | 139.70 | 5 1/2 | 14.29 | 9/16 |
| | 90ARA-A (TR45) | 44.64 | 90.00 | 65.09 | 2 9/16 | 142.88 | 5 5/8 | 130.18 | 5 1/8 | 14.29 | 9/16 |
| | ASCE 85 | 42.17 | 85.00 | 65.09 | 2 9/16 | 131.76 | 5 3/16 | 131.76 | 5 3/16 | 14.29 | 9/16 |
| | ASCE 80 (TR40) | 39.68 | 80.00 | 63.50 | 2 1/2 | 127.00 | 5 | 127.00 | 5 | 13.89 | 35/64 |
| | ASCE 60 (TR30) | 29.76 | 60.00 | 60.32 | 2 3/8 | 107.95 | 4 1/4 | 107.95 | 4 1/4 | 12.30 | 31/64 |
| | ASCE 40 | 19.84 | 40.00 | 47.62 | 1 7/8 | 88.90 | 3 1/2 | 88.90 | 3 1/2 | 9.92 | 25/64 |
| | ASCE 30 | 14.88 | 30.00 | 42.86 | 1 11/16 | 79.37 | 3 1/8 | 79.37 | 3 1/8 | 8.33 | 21/64 |
| | ASCE 25 | 12.40 | 25.00 | 38.10 | 1 1/2 | 69.85 | 2 3/4 | 69.85 | 2 3/4 | 7.54 | 19/64 |
| Perfis europeus | | | | | | | | | | | |
| UIC 860/0 | UIC 60 | 60.34 | 121.64 | 74.30 | 2.93 | 172.00 | 6.77 | 150.00 | 5.91 | 16.50 | 0.65 |
| | UIC 54 | 54.77 | 110.41 | 72.20 | 2.84 | 159.00 | 6.26 | 140.00 | 5.51 | 16.00 | 0.63 |
| DIN | S54 | 54.54 | 109.95 | 70.00 | 2.76 | 154.00 | 6.06 | 125.00 | 4.92 | 16.00 | 0.63 |
| | S49 | 49.43 | 99.65 | 70.00 | 2.76 | 149.00 | 5.87 | 125.00 | 4.92 | 14.00 | 0.55 |